



US009006990B1

(12) **United States Patent**
Timmermans et al.

(10) **Patent No.:** **US 9,006,990 B1**
(45) **Date of Patent:** **Apr. 14, 2015**

(54) **LIGHT TUBE AND POWER SUPPLY CIRCUIT**

(56) **References Cited**

(71) Applicant: **iLumisys, Inc.**, Troy, MI (US)

U.S. PATENT DOCUMENTS

(72) Inventors: **Jos Timmermans**, Ortonville, MI (US);
Jean C. Raymond, Nominique (CA);
John Ivey, Farmington Hills, MI (US)

D84,763 S 7/1931 Strange
D119,797 S 4/1940 Winkler et al.
D125,312 S 2/1941 Logan

(Continued)

(73) Assignee: **iLumisys, Inc.**, Troy, MI (US)

FOREIGN PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

DE 29900320 U1 5/1995
DE 196 51 140 A1 6/1997

(Continued)

(21) Appl. No.: **14/299,909**

OTHER PUBLICATIONS

(22) Filed: **Jun. 9, 2014**

Claim charts submitted in initial invalidity contentions served on May 8, 2014 in Civil Case No. 2:13-cv-14961 (E.D. Mich.) in 174 pages.

(Continued)

Related U.S. Application Data

(63) Continuation of application No. 13/777,331, filed on Feb. 26, 2013, now Pat. No. 8,866,396, which is a continuation of application No. 12/965,019, filed on Dec. 10, 2010, now Pat. No. 8,382,327, which is a

(Continued)

Primary Examiner — Minh D A

(74) *Attorney, Agent, or Firm* — Young Basile

(51) **Int. Cl.**

H05B 37/02 (2006.01)
F21S 4/00 (2006.01)
H05B 33/08 (2006.01)
F21K 99/00 (2010.01)

(52) **U.S. Cl.**

CPC **H05B 33/0815** (2013.01); **F21K 9/17** (2013.01)

(58) **Field of Classification Search**

CPC H05B 37/02; H05B 33/08; H05B 41/36;
F21S 4/001; F21Y 210/00; F21V 29/22
USPC 315/307-308, 312, 185 R, 224, 246,
315/247; 340/240, 249.02, 543, 544, 548,
340/249.03


See application file for complete search history.

(57)

ABSTRACT

A replacement light tube for replacing a fluorescent light tube includes a bulb portion having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube, a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion, a pulse width modulator configured to receive power from a power source and modulate the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level and a current limiter comprising an inductive element coupled between the pulse width modulator and at least some of the plurality of light emitting diodes.

30 Claims, 9 Drawing Sheets



Related U.S. Application Data

continuation of application No. 11/085,744, filed on Mar. 21, 2005, now Pat. No. 8,247,985, which is a continuation of application No. 09/782,375, filed on Feb. 12, 2001, now Pat. No. 7,049,761.

- (60) Provisional application No. 60/181,744, filed on Feb. 11, 2000.

(56)

References Cited

U.S. PATENT DOCUMENTS

2,826,679	A	3/1958	Rosenberg	4,647,217	A	3/1987	Havel
2,909,097	A	10/1959	Alden et al.	4,650,971	A	3/1987	Manecchi et al.
3,178,622	A	4/1965	Paul et al.	4,656,398	A	4/1987	Michael et al.
3,272,977	A	9/1966	Holmes	4,661,890	A	4/1987	Watanabe et al.
3,318,185	A	5/1967	Kott	4,668,895	A	5/1987	Schneiter
3,561,719	A	2/1971	Grindle	4,669,033	A	5/1987	Lee
3,586,936	A	6/1971	McLeroy	4,675,575	A	6/1987	Smith et al.
3,601,621	A	8/1971	Ritchie	4,682,079	A	7/1987	Sanders et al.
3,612,855	A	10/1971	Juhnke	4,686,425	A	8/1987	Havel
3,643,088	A	2/1972	Osteen et al.	4,687,340	A	8/1987	Havel
3,739,336	A	6/1973	Burland	4,688,154	A	8/1987	Nilssen
3,746,918	A	7/1973	Drucker et al.	4,688,869	A	8/1987	Kelly
3,818,216	A	6/1974	Larraburu	4,695,769	A	9/1987	Schweickardt
3,821,590	A	6/1974	Kosman et al.	4,698,730	A	10/1987	Sakai et al.
3,832,503	A	8/1974	Crane	4,701,669	A	10/1987	Head et al.
3,858,086	A	12/1974	Anderson et al.	4,705,406	A	11/1987	Havel
3,909,670	A	9/1975	Wakamatsu et al.	4,707,141	A	11/1987	Havel
3,924,120	A	12/1975	Cox, III	D293,723	S	1/1988	Buttner
3,958,885	A	5/1976	Stockinger et al.	4,727,289	A	2/1988	Uchida
3,969,720	A	7/1976	Nishino	4,727,457	A	2/1988	Thillays
3,974,637	A	8/1976	Bergey et al.	4,739,454	A	4/1988	Federgreen
3,993,386	A	11/1976	Rowe	4,740,882	A	4/1988	Miller
4,001,571	A	1/1977	Martin	4,748,545	A	5/1988	Schmitt
4,009,394	A	2/1977	Mierzwinski	4,753,148	A	6/1988	Johnson
4,054,814	A	10/1977	Fegley et al.	4,758,173	A	7/1988	Northrop
4,070,568	A	1/1978	Gala	4,765,708	A	8/1988	Becker et al.
4,082,395	A	4/1978	Donato et al.	4,767,172	A	8/1988	Hubble, III et al.
4,096,349	A	6/1978	Donato	4,771,274	A	9/1988	Havel
4,102,558	A	7/1978	Krachman	4,780,621	A	10/1988	Bartleucci et al.
4,107,581	A	8/1978	Abernethy	4,794,373	A	12/1988	Harrison
4,189,663	A	2/1980	Schmutzer et al.	4,794,383	A	12/1988	Havel
4,211,955	A	7/1980	Ray	4,801,928	A	1/1989	Minter
4,241,295	A	12/1980	Williams, Jr.	4,810,937	A	3/1989	Havel
4,257,672	A	3/1981	Balliet	4,818,072	A	4/1989	Mohebban
4,261,029	A	4/1981	Mousset	4,824,269	A	4/1989	Havel
4,262,255	A	4/1981	Kokei et al.	4,837,565	A	6/1989	White
4,271,408	A	6/1981	Teshima et al.	4,843,627	A	6/1989	Stebbins
4,271,458	A	6/1981	George, Jr.	4,845,481	A	7/1989	Havel
4,272,689	A	6/1981	Crosby et al.	4,845,745	A	7/1989	Havel
4,273,999	A	6/1981	Pierpoint	4,847,536	A	7/1989	Lowe et al.
4,298,869	A	11/1981	Okuno	4,851,972	A	7/1989	Altman
4,329,625	A	5/1982	Nishizawa et al.	4,854,701	A	8/1989	Noll et al.
4,339,788	A	7/1982	White et al.	4,857,801	A	8/1989	Farrell
4,342,947	A	8/1982	Bloyd	4,863,223	A	9/1989	Weissenbach et al.
4,344,117	A	8/1982	Niccum	4,870,325	A	9/1989	Kazar
4,367,464	A	1/1983	Kurahashi et al.	4,874,320	A	10/1989	Freed et al.
D268,134	S	3/1983	Zurcher	4,887,074	A	12/1989	Simon et al.
4,382,272	A	5/1983	Quella et al.	4,894,832	A	1/1990	Colak
4,388,567	A	6/1983	Yamazaki et al.	4,901,207	A	2/1990	Sato et al.
4,388,589	A	6/1983	Molldrem, Jr.	4,904,988	A	2/1990	Nesbit et al.
4,392,187	A	7/1983	Bornhorst	4,912,371	A	3/1990	Hamilton
4,394,719	A	7/1983	Moberg	4,920,459	A	4/1990	Rothwell et al.
4,420,711	A	12/1983	Takahashi et al.	4,922,154	A	5/1990	Cacoub
4,455,562	A	6/1984	Dolan et al.	4,929,936	A	5/1990	Friedman et al.
4,500,796	A	2/1985	Quin	4,934,852	A	6/1990	Havel
4,521,835	A	6/1985	Meggs et al.	4,941,072	A	7/1990	Yasumoto et al.
4,531,114	A	7/1985	Topol et al.	4,943,900	A	7/1990	Gartner
4,581,687	A	4/1986	Nakanishi	4,962,687	A	10/1990	Belliveau et al.
4,597,033	A	6/1986	Meggs et al.	4,965,561	A	10/1990	Havel
4,600,972	A	7/1986	MacIntyre	4,973,835	A	11/1990	Kurosu et al.
4,607,317	A	8/1986	Lin	4,977,351	A	12/1990	Bavaro et al.
4,622,881	A	11/1986	Rand	4,979,081	A	12/1990	Leach et al.
4,625,152	A	11/1986	Nakai	4,979,180	A	12/1990	Muncheryan
4,635,052	A	1/1987	Aoike et al.	4,980,806	A	12/1990	Taylor et al.
				4,991,070	A	2/1991	Stob
				4,992,704	A	2/1991	Stinson
				5,001,609	A	3/1991	Gardner et al.
				5,003,227	A	3/1991	Nilssen
				5,008,595	A	4/1991	Kazar
				5,008,788	A	4/1991	Palinkas
				5,010,459	A	4/1991	Taylor et al.
				5,018,054	A	5/1991	Ohashi et al.
				5,027,037	A	6/1991	Wei
				5,027,262	A	6/1991	Freed
				5,032,960	A	7/1991	Katoh
				5,034,807	A	7/1991	Von Kohorn
				5,036,248	A	7/1991	McEwan et al.
				5,038,255	A	8/1991	Nishihashi et al.
				5,065,226	A	11/1991	Kluitmans et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

5,072,216	A	12/1991	Grange	5,493,183	A	2/1996	Kimball
5,078,039	A	1/1992	Tulk et al.	5,504,395	A	4/1996	Johnson et al.
5,083,063	A	1/1992	Brooks	5,506,760	A	4/1996	Giebler et al.
5,088,013	A	2/1992	Revis	5,513,082	A	4/1996	Asano
5,089,748	A	2/1992	Ihms	5,519,496	A	5/1996	Borgert et al.
5,103,382	A	4/1992	Kondo et al.	5,530,322	A	6/1996	Ference et al.
5,122,733	A	6/1992	Havel	5,539,628	A	7/1996	Seib
5,126,634	A	6/1992	Johnson	5,544,809	A	8/1996	Keating et al.
5,128,595	A	7/1992	Hara	5,545,950	A	8/1996	Cho
5,130,761	A	7/1992	Tanaka	5,550,440	A	8/1996	Allison et al.
5,130,909	A	7/1992	Gross	5,559,681	A	9/1996	Duarte
5,134,387	A	7/1992	Smith et al.	5,561,346	A	10/1996	Byrne
5,136,483	A	8/1992	Schoniger et al.	D376,030	S	11/1996	Cohen
5,140,220	A	8/1992	Hasegawa	5,575,459	A	11/1996	Anderson
5,142,199	A	8/1992	Elwell	5,575,554	A	11/1996	Guritz
5,151,679	A	9/1992	Dimmick	5,581,158	A	12/1996	Quazi
5,154,641	A	10/1992	McLaughlin	5,592,051	A	1/1997	Korkala
5,161,879	A	11/1992	McDermott	5,592,054	A	1/1997	Nerone et al.
5,161,882	A	11/1992	Garrett	5,600,199	A	2/1997	Martin, Sr. et al.
5,164,715	A	11/1992	Kashiwabara et al.	5,607,227	A	3/1997	Yasumoto et al.
5,184,114	A	2/1993	Brown	5,608,290	A	3/1997	Hutchisson et al.
5,194,854	A	3/1993	Havel	5,614,788	A	3/1997	Mullins et al.
5,198,756	A	3/1993	Jenkins et al.	5,621,282	A	4/1997	Haskell
5,209,560	A	5/1993	Taylor et al.	5,621,603	A	4/1997	Adamec et al.
5,220,250	A	6/1993	Szuba	5,621,662	A	4/1997	Humphries et al.
5,225,765	A	7/1993	Callahan et al.	5,622,423	A	4/1997	Lee
5,226,723	A	7/1993	Chen	5,633,629	A	5/1997	Hochstein
5,254,910	A	10/1993	Yang	5,634,711	A	6/1997	Kennedy et al.
5,256,948	A	10/1993	Boldin et al.	5,639,158	A	6/1997	Sato
5,268,828	A	12/1993	Miura	5,640,061	A	6/1997	Bornhorst et al.
5,278,542	A	1/1994	Smith et al.	5,640,141	A	6/1997	Myllymaki
5,282,121	A	1/1994	Bornhorst et al.	5,640,792	A	6/1997	O'Shea
5,283,517	A	2/1994	Havel	5,642,129	A	6/1997	Zavracky et al.
5,287,352	A	2/1994	Jackson et al.	5,655,830	A	8/1997	Ruskouski
5,294,865	A	3/1994	Haraden	5,656,935	A	8/1997	Havel
5,298,871	A	3/1994	Shimohara	5,661,374	A	8/1997	Cassidy et al.
5,301,090	A	4/1994	Hed	5,661,645	A	8/1997	Hochstein
5,303,124	A	4/1994	Wrobel	5,673,059	A	9/1997	Zavracky et al.
5,307,295	A	4/1994	Taylor et al.	5,682,103	A	10/1997	Burrell
5,321,593	A	6/1994	Moates	5,684,523	A	11/1997	Satoh et al.
5,323,226	A	6/1994	Schreder	5,688,042	A	11/1997	Madadi et al.
5,329,431	A	7/1994	Taylor et al.	5,690,417	A	11/1997	Choate
5,344,068	A	9/1994	Haessig	5,697,695	A	12/1997	Lin et al.
5,350,977	A	9/1994	Hamamoto et al.	5,701,058	A	12/1997	Roth
5,357,170	A	10/1994	Luchaco et al.	5,712,650	A	1/1998	Barlow
5,365,411	A	11/1994	Rycroft et al.	5,713,655	A	2/1998	Blackman
5,371,618	A	12/1994	Tai et al.	5,721,471	A	2/1998	Begemann et al.
5,374,876	A	12/1994	Horibata et al.	5,725,148	A	3/1998	Hartman
5,375,043	A	12/1994	Tokunaga	5,726,535	A	3/1998	Yan
D354,360	S	1/1995	Murata	5,731,759	A	3/1998	Finucan
5,381,074	A	1/1995	Rudzewicz et al.	5,734,590	A	3/1998	Tebbe
5,388,357	A	2/1995	Malita	5,751,118	A	5/1998	Mortimer
5,402,702	A	4/1995	Hata	5,752,766	A	5/1998	Bailey et al.
5,404,094	A	4/1995	Green et al.	5,765,940	A	6/1998	Levy et al.
5,404,282	A	4/1995	Klinke et al.	5,769,527	A	6/1998	Taylor et al.
5,406,176	A	4/1995	Sugden	5,784,006	A	7/1998	Hochstein
5,410,328	A	4/1995	Yoksza et al.	5,785,227	A	7/1998	Akiba
5,412,284	A	5/1995	Moore et al.	5,790,329	A	8/1998	Klaus et al.
5,412,552	A	5/1995	Fernandes	5,803,579	A	9/1998	Turnbull et al.
5,420,482	A	5/1995	Phares	5,803,580	A	9/1998	Tseng
5,421,059	A	6/1995	Leffers, Jr.	5,803,729	A	9/1998	Tsimerman
5,430,356	A	7/1995	Ference et al.	5,806,965	A	9/1998	Deese
5,432,408	A	7/1995	Matsuda et al.	5,808,689	A	9/1998	Small
5,436,535	A	7/1995	Yang	5,810,463	A	9/1998	Kawahara et al.
5,436,853	A	7/1995	Shimohara	5,812,105	A	9/1998	Van de Ven
5,450,301	A	9/1995	Waltz et al.	5,813,751	A	9/1998	Shaffer
5,461,188	A	10/1995	Drago et al.	5,813,753	A	9/1998	Vriens et al.
5,463,280	A	10/1995	Johnson	5,821,695	A	10/1998	Vilanilam et al.
5,463,502	A	10/1995	Savage, Jr.	5,825,051	A	10/1998	Bauer et al.
5,465,144	A	11/1995	Parker et al.	5,828,178	A	10/1998	York et al.
5,473,522	A	12/1995	Kriz et al.	5,831,522	A	11/1998	Weed et al.
5,475,300	A	12/1995	Havel	5,836,676	A	11/1998	Ando et al.
5,481,441	A	1/1996	Stevens	5,841,177	A	11/1998	Komoto et al.
5,489,827	A	2/1996	Xia	5,848,837	A	12/1998	Gustafson
5,491,402	A	2/1996	Small	5,850,126	A	12/1998	Kanbar
				5,851,063	A	12/1998	Doughty et al.
				5,852,658	A	12/1998	Knight et al.
				5,854,542	A	12/1998	Forbes
				RE36,030	E	1/1999	Nadeau

(56)

References Cited

U.S. PATENT DOCUMENTS

5,859,508	A	1/1999	Ge et al.	6,175,220	B1	1/2001	Billig et al.
5,865,529	A	2/1999	Yan	6,181,126	B1	1/2001	Havel
5,870,233	A	2/1999	Benz et al.	D437,947	S	2/2001	Huang
5,890,794	A	4/1999	Abtahi et al.	6,183,086	B1	2/2001	Neubert
5,893,633	A	4/1999	Saito et al.	6,183,104	B1	2/2001	Ferrara
5,896,010	A	4/1999	Mikolajczak et al.	6,184,628	B1	2/2001	Ruthenberg
5,904,415	A	5/1999	Robertson et al.	6,196,471	B1	3/2001	Ruthenberg
5,907,742	A	5/1999	Johnson et al.	6,203,180	B1	3/2001	Fleischmann
5,909,378	A	6/1999	De Milleville	6,211,626	B1	4/2001	Lys et al.
5,912,653	A	6/1999	Fitch	6,215,409	B1	4/2001	Blach
5,917,287	A	6/1999	Haederle et al.	6,217,190	B1	4/2001	Altman et al.
5,917,534	A	6/1999	Rajeswaran	6,219,239	B1	4/2001	Mellberg et al.
5,921,660	A	7/1999	Yu	6,227,679	B1	5/2001	Zhang et al.
5,924,784	A	7/1999	Chliwnyj et al.	6,234,645	B1	5/2001	Börner et al.
5,927,845	A	7/1999	Gustafson et al.	6,238,075	B1	5/2001	Dealey, Jr. et al.
5,934,792	A	8/1999	Camarota	6,240,665	B1	6/2001	Brown et al.
5,936,599	A	8/1999	Reymond	6,241,359	B1	6/2001	Lin
5,939,830	A	* 8/1999	Praiswater 315/169.3	6,249,221	B1	6/2001	Reed
5,943,802	A	8/1999	Tijanac	6,250,774	B1	6/2001	Begemann et al.
5,946,209	A	8/1999	Eckel et al.	6,252,350	B1	6/2001	Alvarez
5,949,347	A	9/1999	Wu	6,252,358	B1	6/2001	Xydis et al.
5,951,145	A	9/1999	Iwasaki et al.	6,268,600	B1	7/2001	Nakamura et al.
5,952,680	A	9/1999	Strite	6,273,338	B1	8/2001	White
5,959,547	A	9/1999	Tubel et al.	6,292,901	B1	9/2001	Lys et al.
5,961,072	A	10/1999	Bodle	6,297,724	B1	10/2001	Bryans et al.
5,962,989	A	10/1999	Baker	6,305,109	B1	10/2001	Lee
5,962,992	A	10/1999	Huang et al.	6,305,821	B1	10/2001	Hsieh et al.
5,963,185	A	10/1999	Havel	6,307,331	B1	10/2001	Bonasia et al.
5,966,069	A	10/1999	Zmurk et al.	6,310,590	B1	10/2001	Havel
5,974,553	A	10/1999	Gandar	6,315,429	B1	11/2001	Grandolfo
5,980,064	A	11/1999	Metroyanis	6,323,832	B1	11/2001	Nishizawa et al.
5,998,925	A	12/1999	Shimizu et al.	6,325,651	B1	12/2001	Nishihara et al.
5,998,928	A	12/1999	Hipp	6,334,699	B1	1/2002	Gladnick
6,000,807	A	12/1999	Moreland	6,340,868	B1	1/2002	Lys et al.
6,007,209	A	12/1999	Pelka	6,362,578	B1	3/2002	Swanson et al.
6,008,783	A	12/1999	Kitagawa et al.	6,371,637	B1	4/2002	Atchinson et al.
6,010,228	A	1/2000	Blackman et al.	6,380,865	B1	4/2002	Pederson
6,011,691	A	1/2000	Schreffler	6,394,623	B1	5/2002	Tsui
6,016,038	A	1/2000	Mueller et al.	6,400,096	B1	6/2002	Wells et al.
6,018,237	A	1/2000	Havel	6,404,131	B1	6/2002	Kawano et al.
6,019,493	A	2/2000	Kuo et al.	6,411,045	B1	6/2002	Nerone
6,020,825	A	2/2000	Chansky et al.	6,429,604	B1	8/2002	Chang
6,025,550	A	2/2000	Kato	6,445,139	B1	9/2002	Marshall et al.
6,028,694	A	2/2000	Schmidt	6,459,919	B1	10/2002	Lys et al.
6,030,099	A	2/2000	McDermott	6,464,373	B1	10/2002	Petrick
6,031,343	A	2/2000	Recknagel et al.	6,469,457	B2	10/2002	Callahan
6,031,958	A	2/2000	McGaffigan	6,471,388	B1	10/2002	Marsh
6,036,335	A	3/2000	Openiano	6,495,964	B1	12/2002	Muthu et al.
6,036,636	A	3/2000	Konomura et al.	6,511,204	B2	1/2003	Emmel et al.
D422,737	S	4/2000	Orozco	6,528,954	B1	3/2003	Lys et al.
6,056,420	A	5/2000	Wilson et al.	6,540,381	B1	4/2003	Douglass, II
6,068,383	A	5/2000	Robertson et al.	6,541,800	B2	4/2003	Barnett et al.
6,069,597	A	5/2000	Hansen	6,548,967	B1	4/2003	Dowling et al.
6,072,280	A	6/2000	Allen	6,568,834	B1	5/2003	Scianna
6,084,359	A	7/2000	Hetzel et al.	6,577,072	B2	6/2003	Saito et al.
6,086,220	A	7/2000	Lash et al.	6,577,080	B2	6/2003	Lys et al.
6,091,200	A	7/2000	Lenz	6,577,794	B1	6/2003	Currie et al.
6,092,915	A	7/2000	Rensch	6,582,103	B1	6/2003	Popovich et al.
6,095,661	A	8/2000	Lebens et al.	6,585,393	B1	7/2003	Brandes et al.
6,097,352	A	8/2000	Zavracky et al.	6,608,453	B2	8/2003	Morgan et al.
6,115,184	A	9/2000	Hubble, III et al.	6,609,813	B1	8/2003	Showers et al.
6,116,748	A	9/2000	George	6,612,729	B1	9/2003	Hoffman
6,121,875	A	9/2000	Hamm et al.	6,621,222	B1	9/2003	Hong
6,127,783	A	10/2000	Pashley et al.	6,624,597	B2	9/2003	Dowling et al.
6,132,072	A	10/2000	Turnbull et al.	6,682,205	B2	1/2004	Lin
6,135,604	A	10/2000	Lin	6,712,486	B1	3/2004	Popovich et al.
6,135,620	A	10/2000	Marsh	6,717,376	B2	4/2004	Lys et al.
6,139,174	A	10/2000	Butterworth	6,720,745	B2	4/2004	Lys et al.
6,149,283	A	11/2000	Conway et al.	6,736,525	B2	5/2004	Chin
6,150,774	A	11/2000	Mueller et al.	6,762,562	B2	7/2004	Leong
6,151,529	A	11/2000	Batko	6,768,047	B2	7/2004	Chang et al.
6,153,985	A	11/2000	Grossman	6,774,584	B2	8/2004	Lys et al.
6,158,882	A	12/2000	Bischoff, Jr.	6,777,891	B2	8/2004	Lys et al.
6,166,496	A	12/2000	Lys et al.	6,781,329	B2	8/2004	Mueller et al.
6,175,201	B1	1/2001	Sid	6,788,011	B2	9/2004	Mueller et al.
				6,796,680	B1	9/2004	Showers et al.
				6,806,659	B1	10/2004	Mueller et al.
				6,853,151	B2	2/2005	Leong et al.
				6,869,204	B2	3/2005	Morgan et al.

(56)

References Cited

FOREIGN PATENT DOCUMENTS


JP	08-162677	A	6/1996
JP	H8-162677		6/1996
JP	10-308536	A	11/1998
JP	H11-135274		5/1999
JP	11-162234	A	6/1999
JP	H11-162234	A	6/1999
JP	H11-260125	A	9/1999
JP	5102530	B2	12/2012
WO	99/06759	A1	2/1999
WO	99/10867	A1	3/1999
WO	99/31560	A2	6/1999
WO	99/45312	A1	9/1999
WO	99/57945	A1	11/1999
WO	00/01067	A2	1/2000

OTHER PUBLICATIONS

Petition for Inter Partes Review of U.S. Patent No. 8093823, IPR # 2014-00448 filed Feb. 19, 2014 in 1175 pages. (uploaded in three parts due to EFS size limits).
 Lighting Handbook, 8th Edition, Illuminating Engineering Society of North America, 1993, pp. 237-240.
 Petition for Inter Partes Review of U.S. Patent No. 7,510,299, IPR # 2014-00710 filed Apr. 30, 2014 in 2135 pages. (uploaded in ten parts due to EFS size limits).

Defendant's Invalidation Contentions in *Altair Engineering, Inc. v. LEDSAmerica, Inc.*, Civil Case No. 2:10-CV-13424 (E. D. Mich.)(J. O'Meara)(Feb. 4, 2011).
 Decision in *Altair Engineering, Inc. v. LEDdynamics* (Fed. Cir. Mar. 9, 2011).
 Web page at http://trucklite.com/leds_14.htm printed on Jan. 13, 2000.
 Web page at http://trucklite.com/leds_2.htm printed on Jan. 13, 2000.
 Web page at http://trucklite.com/leds_4.htm printed on Jan. 13, 2000.
 Web page at http://www.telecite.com/en/products/options_en.htm printed on Jan. 13, 2000.
 Web page at <http://www.dialight.com/trans.htm> printed on Jan. 13, 2000.
 Web page at <http://www.ledlight.com/replac.htm> printed on Jan. 13, 2000.
 Ledtronics, apparently 1996 Catalog, apparently cover page and p. 10.
 Petition for Inter Partes Review of U.S. Patent No. 8,382,327, IPR # 2014-01120 filed Jul. 3, 2014 in 854 pages. (uploaded in fifteen parts due to EFS size limits).
 Petition for Inter Partes Review of U.S. Patent No. 7,049,761, IPR # 2014-01333 filed Aug. 19, 2014 in 757 pages. (uploaded in ten parts due to EFS size limits).
 * cited by examiner

FIG-1






FIG-2




FIG-3




FIG-4




FIG-5




FIG-6





FIG-7






FIG-9




FIG-10

1

LIGHT TUBE AND POWER SUPPLY CIRCUIT**CROSS-REFERENCE TO RELATED APPLICATIONS**

This application is a continuation of U.S. patent application Ser. No. 13/777,331, filed Feb. 26, 2013, which is a continuation of U.S. patent application Ser. No. 12/965,019, filed Dec. 10, 2010 and issued as U.S. Pat. No. 8,382,327 on Feb. 26, 2013, which is a continuation of U.S. patent application Ser. No. 11/085,744, filed Mar. 21, 2005 and issued as U.S. Pat. No. 8,247,985 on Aug. 21, 2012, which is a continuation of U.S. patent application Ser. No. 09/782,375, filed Feb. 12, 2001 and issued as U.S. Pat. No. 7,049,761 on May 23, 2006, which claims the benefit of U.S. Provisional Application No. 60/181,744 filed Feb. 11, 2000.

FIELD OF THE INVENTION

The present invention relates to a light tube illuminated by LEDs (light emitting diodes) which are packaged inside the light tube and powered by a power supply circuit.

BACKGROUND OF THE INVENTION

Conventional fluorescent lighting systems include fluorescent light tubes and ballasts. Such lighting systems are used in a variety of locations, such as buildings and transit buses, for a variety of lighting purposes, such as area lighting or back-lighting. Although conventional fluorescent lighting systems have some advantages over known lighting options, such as incandescent lighting systems, conventional fluorescent light tubes and ballasts have several shortcomings. Conventional fluorescent light tubes have a short life expectancy, are prone to fail when subjected to excessive vibration, consume high amounts of power, require a high operating voltage, and include several electrical connections which reduce reliability. Conventional ballasts are highly prone to fail when subjected to excessive vibration. Accordingly, there is a desire to provide a light tube and power supply circuit which overcome the shortcomings of conventional fluorescent lighting systems. That is, there is a desire to provide a light tube and power supply circuit which have a long life expectancy, are resistant to vibration failure, consume low amounts of power, operate on a low voltage, and are highly reliable. It would also be desirable for such a light tube to mount within a conventional fluorescent light tube socket.

SUMMARY OF THE INVENTION

Embodiments of a replacement light tube for replacing a fluorescent light tube are disclosed herein. In one embodiment, the replacement light tube includes a bulb portion having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube and a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion. The plurality of light emitting diodes are arranged to provide light through at least a portion of the bulb portion. The replacement light tube also includes a pulse width modulator configured to receive power from a power source and modulate the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level and a current limiter comprising an inductive element

2

coupled between the pulse width modulator and at least some of the plurality of light emitting diodes.

In another embodiment, the replacement light tube includes a housing having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube and a rigid support structure having a planar portion having a first surface extending within the housing between the first end and the second end and having spaced-apart sidewalls extending away from the first surface and extending within the housing between the first end and the second end. At least a portion of the sidewalls are in contact with an interior surface of the housing. The replacement light tube also includes a plurality of light emitting diodes supported by a second surface of the planar portion opposite to the first surface and extending between the first and second ends of the housing. The plurality of light emitting diodes are arranged to provide light through at least a portion of the housing. Further, the replacement light tube includes power supply circuitry configured to receive power from a power source and modulate the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level.

In another embodiment, the replacement light tube is configured to emit white light at a plurality of brightness levels and includes a housing having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube and a plurality of light emitting diodes disposed inside and extending between the first and second ends of the housing. The plurality of light emitting diodes are arranged to provide light through at least a portion of the housing. The replacement light tube also includes a pulse width modulator configured to: receive power from a power source, in response to a first user adjustment, modulate the received power to a first one of the plurality of brightness levels, and in response to a second user adjustment, modulate the received power to a second one of the plurality of brightness levels, wherein the second brightness level is different than the first brightness level. Further, the replacement light tube includes a current limiter comprising an inductive element coupled between the pulse width modulator and at least some of the plurality of light emitting diodes.

Embodiments of a method for operating a replacement light tube for replacing a fluorescent light tube are disclosed herein where the replacement light tube includes a bulb portion having a first end and a second end, a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube, a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion and power supply circuitry having a pulse-width modulator and a current limiting circuit including an inductive element coupled between pulse-width modulator and at least some of the plurality of light emitting diodes. In one embodiment, the method includes receiving power from a power source and modulating, using the pulse-width modulator, the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level.

These and other embodiments will be discussed in additional detail hereafter.

BRIEF DESCRIPTION OF THE DRAWINGS

The description herein makes reference to the accompanying drawings wherein like reference numerals refer to like parts throughout the several views, and wherein:

3

FIG. 1 is a line drawing showing a light tube, in perspective view, which in accordance with the present invention is illuminated by LEDs packaged inside the light tube;

FIG. 2 is a perspective view of the LEDs mounted on a circuit board;

FIG. 3 is a cross-sectional view of FIG. 2 taken along lines 3-3;

FIG. 4 is a fragmentary, perspective view of one embodiment of the present invention showing one end of the light tube disconnected from one end of a light tube socket;

FIG. 5 is an electrical block diagram of a first power supply circuit for supplying power to the light tube;

FIG. 6 is an electrical schematic of a switching power supply type current limiter;

FIG. 7 is an electrical block diagram of a second power supply circuit for supplying power to the light tube;

FIG. 8 is an electrical block diagram of a third power supply circuit for supplying power to the light tube;

FIG. 9 is a fragmentary, perspective view of another embodiment of the present invention showing one end of the light tube disconnected from one end of the light tube socket; and

FIG. 10 is an electrical block diagram of a fourth power supply circuit for supplying power to the light tube.

DETAILED DESCRIPTION

FIG. 1 is a line drawing showing a light tube 20 in perspective view. In accordance with the present invention, the light tube 20 is illuminated by LEDs 22 packaged inside the light tube 20. The light tube 20 includes a cylindrically shaped bulb portion 24 having a pair of end caps 26 and 28 disposed at opposite ends of the bulb portion. Preferably, the bulb portion 24 is made from a transparent or translucent material such as glass, plastic, or the like. As such, the bulb material may be either clear or frosted.

In a preferred embodiment of the present invention, the light tube 20 has the same dimensions and end caps 26 and 28 (e.g. electrical male bi-pin connectors, type G13) as a conventional fluorescent light tube. As such, the present invention can be mounted in a conventional fluorescent light tube socket.

The line drawing of FIG. 1 also reveals the internal components of the light tube 20. The light tube 20 further includes a circuit board 30 with the LEDs 22 mounted thereon. The circuit board 30 and LEDs 22 are enclosed inside the bulb portion 24 and the end caps 26 and 28.

FIG. 2 is a perspective view of the LEDs 22 mounted on the circuit board 30. A group of LEDs 22, as shown in FIG. 2, is commonly referred to as a bank or array of LEDs. Within the scope of the present invention, the light tube 20 may include one or more banks or arrays of LEDs 22 mounted on one or more circuit boards 30. In a preferred embodiment of the present invention, the LEDs 22 emit white light and, thus, are commonly referred to in the art as white LEDs. In FIGS. 1 and 2, the LEDs 22 are mounted to one surface 32 of the circuit board 30. In a preferred embodiment of the present invention, the LEDs 22 are arranged to emit or shine white light through only one side of the bulb portion 24, thus directing the white light to a predetermined point of use. This arrangement reduces light losses due to imperfect reflection in a conventional lighting fixture. In alternative embodiments of the present invention, LEDs 22 may also be mounted, in any combination, to the other surfaces 34, 36, and/or 38 of the circuit board 30.

FIG. 3 is a cross-sectional view of FIG. 2 taken along lines 3-3. To provide structural strength along the length of the light

4

tube 20, the circuit board 30 is designed with a H-shaped cross-section. To produce a predetermined radiation pattern or dispersion of light from the light tube 20, each LED 22 is mounted at an angle relative to adjacent LEDs and/or the mounting surface 32. The total radiation pattern of light from the light tube 20 is effected by (1) the mounting angle of the LEDs 22 and (2) the radiation pattern of light from each LED. Currently, white LEDs having a viewing range between 6° and 45° are commercially available.

FIG. 4 is a fragmentary, perspective view of one embodiment of the present invention showing one end of the light tube 20 disconnected from one end of a light tube socket 40. Similar to conventional fluorescent lighting systems and in this embodiment of the present invention, the light tube socket 40 includes a pair of electrical female connectors 42 and the light tube 20 includes a pair of mating electrical male connectors 44.

Within the scope of the present invention, the light tube 20 may be powered by one of four power supply circuits 100, 200, 300, and 400. A first power supply circuit includes a power source and a conventional fluorescent ballast. A second power supply circuit includes a power source and a rectifier/filter circuit. A third power supply circuit includes a DC power source and a PWM (Pulse Width Modulation) circuit. A fourth power supply circuit powers the light tube 20 inductively.

FIG. 5 is an electrical block diagram of a first power supply circuit 100 for supplying power to the light tube 20. The first power supply circuit 100 is particularly adapted to operate within an existing, conventional fluorescent lighting system. As such, the first power supply circuit 100 includes a conventional fluorescent light tube socket 40 having two electrical female connectors 42 disposed at opposite ends of the socket. Accordingly, a light tube 20 particularly adapted for use with the first power supply circuit 100 includes two end caps 26 and 28, each end cap having the form of an electrical male connector 44 which mates with a corresponding electrical female connector 42 in the socket 40.

The first power supply circuit 100 also includes a power source 46 and a conventional magnetic or electronic fluorescent ballast 48. The power source 46 supplies power to the conventional fluorescent ballast 48.

The first power supply circuit 100 further includes a rectifier/filter circuit 50, a PWM circuit 52, and one or more current-limiting circuits 54. The rectifier/filter circuit 50, the PWM circuit 52, and the one or more current-limiting circuits 54 of the first power supply circuit 100 are packaged inside one of the two end caps 26 or 28 of the light tube 20.

The rectifier/filter circuit 50 receives AC power from the ballast 48 and converts the AC power to DC power. The PWM circuit 52 receives the DC power from the rectifier/filter circuit 50 and pulse-width modulates the DC power to the one or more current-limiting circuits 54. In a preferred embodiment of the present invention, the PWM circuit 52 receives the DC power from the rectifier/filter circuit 50 and cyclically switches the DC power on and off to the one or more current-limiting circuits 54. The DC power is switched on and off by the PWM circuit 52 at a frequency which causes the white light emitted from the LEDs 22 to appear, when viewed with a "naked" human eye, to shine continuously. The PWM duty cycle can be adjusted or varied by control circuitry (not shown) to maintain the power consumption of the LEDs 22 at safe levels.

The DC power is modulated for several reasons. First, the DC power is modulated to adjust the brightness or intensity of the white light emitted from the LEDs 22 and, in turn, adjust the brightness or intensity of the white light emitted from the

light tube 20. Optionally, the brightness or intensity of the white light emitted from the light tube 20 may be adjusted by a user. Second, the DC power is modulated to improve the illumination efficiency of the light tube 20 by capitalizing upon a phenomenon in which short pulses of light at high brightness or intensity to appear brighter than a continuous, lower brightness or intensity of light having the same average power. Third, the DC power is modulated to regulate the intensity of light emitted from the light tube 20 to compensate for supply voltage fluctuations, ambient temperature changes, and other such factors that affect the intensity of white light emitted by the LEDs 22. Fourth, the DC power is modulated to raise the variations of the frequency of light above the nominal variation of 120 to 100 Hz thereby reducing illumination artifacts caused by low frequency light variations, including interactions with video screens. Fifth, the DC power may optionally be modulated to provide an alarm function wherein light from the light tube 20 cyclically flashes on and off.

The one or more current-limiting circuits 54 receive the pulse-width modulated or switched DC power from the PWM circuit 52 and transmit a regulated amount of power to one or more arrays of LEDs 22. Each current-limiting circuit 54 powers a bank of one or more white LEDs 22. If a bank of LEDs 22 consists of more than one LED, the LEDs are electrically connected in series in an anode to cathode arrangement. If brightness or intensity variation between the LEDs 22 can be tolerated, the LEDs can be electrically connected in parallel.

The one or more current-limiting circuits 54 may include (1) a resistor, (2) a current-limiting semiconductor circuit, or (3) a switching power supply type current limiter.

FIG. 6 is an electrical schematic of a switching power supply type current limiter 56. The limiter 56 includes an inductor 58, electrically connected in series between the PWM circuit 52 and the array of LEDs 22, and a power diode 60, electrically connected between ground 62 and a PWM circuit/inductor node 64. The diode 60 is designed to begin conduction after the PWM circuit 52 is switched off. In this case, the value of the inductor 58 is adjusted in conjunction with the PWM duty cycle to provide the benefits described above. The switching power supply type current limiter 56 provides higher power efficiency than the other types of current-limiting circuits listed above.

FIG. 7 is an electrical block diagram of a second power supply circuit 200 for supplying power to the light tube 20. Similar to the first power supply circuit 100, the second power supply circuit 200 includes a conventional fluorescent light tube socket 40 having two electrical female connectors 42 disposed at opposite ends of the socket 40. Accordingly, a light tube 20 particularly adapted for use with the second power supply circuit 200 includes two end caps 26 and 28, each end cap having the form of an electrical male connector 44 which mates with a corresponding electrical female connector 42 in the socket 40.

In the second power supply circuit 200, the power source 46 supplies power directly to the rectifier/filter circuit 50. The rectifier/filter circuit 50, the PWM circuit 52, and the one or more current-limiting circuits 54 operate as described above to power the one or more arrays of LEDs 22. The rectifier/filter circuit 50, the PWM circuit 52, and the one or more current-limiting circuits 54 of the second power supply circuit 200 are preferably packaged inside the end caps 26 and 28 or the bulb portion 24 of the light tube 20 or inside the light tube socket 40.

FIG. 8 is an electrical block diagram of a third power supply circuit 300 for supplying power to the light tube 20.

Similar to the first and second power supply circuits 100 and 200, the third power supply circuit 300 includes a conventional fluorescent light tube socket 40 having two electrical female connectors 42 disposed at opposite ends of the socket 40. Accordingly, a light tube 20 particularly adapted for use with the third power supply circuit 300 includes two end caps 26 and 28, each end cap having the form of an electrical male connector 44 which mates with a corresponding electrical female connector 42 in the socket 40.

The third power supply circuit 300 includes a DC power source 66, such as a vehicle battery. In the third power supply circuit 300, the DC power source 66 supplies DC power directly to the PWM circuit 52. The PWM circuit 52 and the one or more current-limiting circuits 54 operate as described above to power the one or more arrays of LEDs 22. In the third power supply circuit 300, the PWM circuit 52 is preferably packaged in physical location typically occupied by the ballast of a conventional fluorescent lighting system while the one or more current-limiting circuits 54 and LEDs 22 are preferably packaged inside the light tube 20, in either one of the two end caps 26 or 28 or the bulb portion 24.

FIG. 9 is a fragmentary, perspective view of another embodiment of the present invention showing one end of the light tube 20 disconnected from one end of the light tube socket 40. In this embodiment of the present invention, the light tube socket 40 includes a pair of brackets 68 and the light tube 20 includes a pair of end caps 26 and 28 which mate with the brackets 68.

FIG. 10 is an electrical block diagram of a fourth power supply circuit 400 for supplying power to the light tube 20. Unlike the first, second, and third power supply circuits 100, 200, and 300 which are powered through direct electrical male and female connectors 44 and 42, the fourth power supply circuit 400 is powered inductively. As such, the fourth power supply circuit 400 includes a light tube socket 40 having two brackets 68 disposed at opposite ends of the socket 40. At least one bracket 68 includes an inductive transmitter 70. Accordingly, a light tube 20 particularly adapted for use with the fourth power supply circuit 400 has two end caps 26 and 28 with at least one end cap including an inductive receiver or antenna 72. When the light tube 20 is mounted in the light tube socket 40, the at least one inductive receiver 72 in the light tube 20 is disposed adjacent to the at least one inductive transmitter 70 in the light tube socket 40.

The fourth power supply circuit 400 includes the power source 46 which supplies power to the at least one inductive transmitter 70 in the light tube socket 40. The at least one transmitter 70 inductively supplies power to the at least one receiver 72 in one of the end caps 26 and/or 28 of the light tube 20. The at least one inductive receiver 72 supplies power to the rectifier/filter circuit 50. The rectifier/filter circuit 50, PWM circuit 52, and the one or more current-limiting circuits 54 operate as described above to power the one or more arrays of LEDs 22. In this manner, the light tube 20 is powered without direct electrical connection.

What is claimed is:

1. A replacement light tube for replacing a fluorescent light tube, comprising:
 - a bulb portion having a first end and a second end;
 - a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;
 - a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion, wherein the plurality of light emitting diodes are arranged to provide light through at least a portion of the bulb portion;

7

a pulse width modulator configured to receive power from a power source and modulate the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level; and

a current limiter comprising an inductive element coupled between the pulse width modulator and at least some of the plurality of light emitting diodes.

2. The replacement light tube of claim 1, wherein the first and second brightness levels correspond to different brightness or intensity levels of white light emitted from the replacement light tube.

3. The replacement light tube of claim 1, wherein the pulse width modulator is configured to modulate the received power to one of the first and second brightness levels based on an adjustment made by a user.

4. The replacement light tube of claim 1, wherein the first brightness level corresponds to an off state and the second brightness level corresponds to an on state.

5. The replacement light tube of claim 1, wherein the pulse width modulator is configured to supply the modulated power at the first brightness level to the plurality of light emitting diodes.

6. The replacement light tube of claim 5, wherein the pulse width modulator is configured to supply the modulated power at the second brightness level to the plurality of light emitting diodes.

7. The replacement light tube of claim 1, wherein the pulse width modulator is configured to modulate the received power to one of the first and second brightness levels without an adjustment made by a user.

8. A replacement light tube for replacing a fluorescent light tube, comprising:

a housing having a first end and a second end;
a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;

a rigid support structure having a planar portion having a first surface extending within the housing between the first end and the second end and having spaced-apart sidewalls extending away from the first surface and extending within the housing between the first end and the second end, at least a portion of the sidewalls in contact with an interior surface of the housing;

a plurality of light emitting diodes supported by a second surface of the planar portion opposite to the first surface and extending between the first and second ends of the housing, wherein the plurality of light emitting diodes are arranged to provide light through at least a portion of the housing; and

power supply circuitry configured to receive power from a power source and modulate the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level.

9. The replacement light tube of claim 8, wherein the first and second brightness levels correspond to different brightness or intensity levels of white light emitted from the replacement light tube.

10. The replacement light tube of claim 8, wherein the pulse width modulator is configured to modulate the received power to one of the first and second brightness levels based on an adjustment made by a user.

11. The replacement light tube of claim 8, wherein the first brightness level corresponds to an off state and the second brightness level corresponds to an on state.

8

12. The replacement light tube of claim 8, wherein the pulse width modulator is configured to supply the modulated power at the first brightness level to the plurality of light emitting diodes.

13. The replacement light tube of claim 12, wherein the pulse width modulator is configured to supply the modulated power at the second brightness level to the plurality of light emitting diodes.

14. The replacement light tube of claim 8, further comprising:

a current limiter comprising an inductive element coupled between the pulse width modulator and at least some of the plurality of light emitting diodes.

15. The replacement light tube of claim 8, wherein the pulse width modulator is configured to modulate the received power to one of the first and second brightness levels without an adjustment made by a user.

16. The replacement light tube of claim 8, wherein the planar portion is integral with the sidewalls.

17. The replacement light tube of claim 8, wherein the sidewalls each have a substantially uniform cross-section along a length of the housing.

18. A method for operating a replacement light tube for replacing a fluorescent light tube, the replacement light tube including:

a bulb portion having a first end and a second end;
a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;

a plurality of light emitting diodes disposed inside and extending between the first and second ends of the bulb portion; and

power supply circuitry having a pulse-width modulator and a current limiting circuit including an inductive element coupled between pulse-width modulator and at least some of the plurality of light emitting diodes, the method comprising:

receiving power from a power source; and
modulating, using the pulse-width modulator, the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level.

19. The method for operating the replacement light tube of claim 18, wherein the first and second brightness levels correspond to different brightness or intensity levels of white light emitted from the replacement light tube.

20. The method for operating the replacement light tube of claim 18, wherein modulating the received power further comprises:

modulating, using the pulse-width modulator, the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level based an adjustment made by a user.

21. The method for operating the replacement light tube of claim 18, wherein the first brightness level corresponds to an off state and the second brightness level corresponds to an on state.

22. The method for operating the replacement light tube of claim 18, further comprising:

supplying the modulated power at the first brightness level to the plurality of light emitting diodes.

23. The method for operating the replacement light tube of claim 22, further comprising:

supplying the modulated power at the second brightness level to the plurality of light emitting diodes.

24. The method for operating the replacement light tube of claim 18, wherein modulating the received power further comprises:

modulating, using the pulse-width modulator, the received power to one of a first brightness level and a second brightness level, the second brightness level being different than the first brightness level without an adjustment made by a user.

25. A replacement light tube for replacing a fluorescent light tube, the replacement light tube configured to emit white light at a plurality of brightness levels, comprising:

a housing having a first end and a second end;
 a first end cap and a second end cap disposed at the first end and the second end, respectively, each configured to fit with a socket for the fluorescent light tube;

a plurality of light emitting diodes disposed inside and extending between the first and second ends of the housing, wherein the plurality of light emitting diodes are arranged to provide light through at least a portion of the housing;

a pulse width modulator configured to:
 receive power from a power source,
 in response to a first user adjustment, modulate the received power to a first one of the plurality of brightness levels, and
 in response to a second user adjustment, modulate the received power to a second one of the plurality of brightness levels, wherein the second brightness level is different than the first brightness level; and

a current limiter comprising an inductive element coupled between the pulse width modulator and at least some of the plurality of light emitting diodes.

26. The replacement light tube of claim 25, wherein the first and second brightness levels correspond to different brightness or intensity levels of white light emitted from the replacement light tube.

27. The replacement light tube of claim 25, wherein the first brightness level corresponds to an off state and the second brightness level corresponds to an on state.

28. The replacement light tube of claim 25, wherein the pulse width modulator is configured to supply the modulated power at the first brightness level to the plurality of light emitting diodes.

29. The replacement light tube of claim 28, wherein the pulse width modulator is configured to supply the modulated power at the second brightness level to the plurality of light emitting diodes.

30. The replacement light tube of claim 25, further comprising:

a rigid support structure having a planar portion having a first surface extending within the housing between the first end and the second end and having spaced-apart sidewalls extending away from the first surface and extending within the housing between the first end and the second end, at least a portion of the sidewalls in contact with an interior surface of the housing, wherein at least a portion of the sidewalls is in contact with an interior surface of the elongate tubular housing.

* * * * *